



Special Purpose Tile & Flooring Adhesive

Clear

- Will withstand expansion/contraction with minimal gapping
- Ideal for Vinyl Tile Applications
- No Cupping in Hardwood Floor applications
- One-Sided Application
- Quick Tacking (5-30 seconds)
- Bond can Withstand Heat and Humidity
- High & Long Lasting Tack
- Good For Floors and Walls
- Waterproof, Non-Staining
- HAPs free (no hazardous air pollutants)
- No ODS (no ozone depleting substances)

At Westech, our efforts are focused on producing high quality, industrial strength adhesives. We sell our products in a wide variety of markets at a competitive price. With a profound understanding of our customers' needs and years of industry experience, we continue to develop new products and applications to serve our current and future customers.

Westech's VersaTILE was formulated for bonding a variety of materials in general construction. It is a multi-purpose industrial strength, high temperature adhesive. Industries for which this adhesive is suitable include general construction, furniture, RV, upholstery and many others.

VersaTILE provides a fast tacking, strong, permanent and waterproof bond for construction and refurbishment related applications.

- Vinyl Tile
- Wall Coverings
- FRP (fiberglass reinforced plastic panels)
- Carpet
- Fabrics
- Metals

Technical Data

Westech VersaTILE product is formulated as a non-methylene chloride, solvent-based, multi-purpose adhesive for industrial use.

Technical Data:

- Contains NO CFCs, no ODS (no Ozone Depleting Substances)

Performance Features:

- Formulated for rapid application
- Bond will hold in the presence of both heat and humidity
- Applies easily and adheres to a variety of substrates

Safety Recommendations:

Vapors may be harmful to health. Keep away from children. Use only in well ventilated areas or use respiratory protection. The product MSDS should be read and understood before use. Eye protection is required. This product is flammable. Keep away from fire or flame.

Recommended Usage:

Not for use on expanded polystyrene (EPS) foams. VersaTILE is designed as a one-sided spray application. Surface must be clean of dust and dirt, and substrates should be properly acclimated. Surface preparation is very important. Sanding substrate relatively smooth to facilitate adhesive contact and avoid substrate projections and excess adhesive depth / usage is very important. Prior to use, a small test patch should be sprayed to evaluate substrate compatibility. This product may degrade some thin plastics and films.



5405 CONSTANCE DR. SW * PORT ORCHARD, WA 98367
TEL: 877-674-2010 * FAX: 360-674-2053
WWW.OK2SPRAY.COM

Industrial Strength Contact Adhesive